



PCT

WORLD INTELLECTUAL
PROPERTY ORGANIZATION

WO 9604738A1

INTERNATIONAL APPLICATION PUBLISHED

(51) International Patent Classification 6:

H04L 25/03, H04B 7/08

A1

(11) International Publication Number:

WO 96/04738

(43) International Publication Date:

15 February 1996 (15.02.96)

(21) International Application Number: PCT/US95/09484

(22) International Filing Date: 28 July 1995 (28.07.95)

(30) Priority Data:

284,775

2 August 1994 (02.08.94)

US

(71) Applicant: ERICSSON INC. [US/US]; 1 Triangle Drive,
Research Triangle Park, NC 27709 (US).(72) Inventor: BOTTOMLEY, Gregory, E.; 100 Merlot Court,
Cary, NC 27703 (US).(74) Agent: LASTOVA, John, R.; Nixon & Vanderhye PC, 8th
floor, 1100 North Glebe Road, Arlington, VA 22201-4714
(US).


(81) Designated States: AM, AT, AU, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LT, LU, LV, MD, MG, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TT, UA, UG, UZ, VN, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG), ARIPO patent (KE, MW, SD, SZ, UG).

Published

With international search report.

Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

(54) Title: METHOD OF AND APPARATUS FOR INTERFERENCE REJECTION COMBINING IN MULTI-ANTENNA DIGITAL CELLULAR COMMUNICATIONS SYSTEMS



(57) Abstract

A digital radio communications system is presented in which the deleterious effects of fading, time dispersion and interference found in the channel are mitigated by using interference rejection and diversity combining. Digital signals representative of digital symbol sequences are transmitted through a radio channel in which the signals may be corrupted by fading, time dispersion and interference. The corrupted signals are received by a receiver having one or more antennas. The received signals are processed to form a received signal sample stream $r_d(kT_s)$ for each of the antennas. Estimated received signal samples for each of the antennas are produced by combining hypothesized signal sequences and models of each channel. The received signal samples and the estimated received signal samples are processed in conjunction with an estimate of the impairment correlation properties to produce branch metrics to be used by a Viterbi, or other sequence estimation, algorithm. The branch metric processor may assume one of several configurations depending on whether or not the channel is time-varying.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

METHOD OF AND APPARATUS FOR INTERFERENCE REJECTION COMBINING IN MULTI-ANTENNA DIGITAL CELLULAR COMMUNICATIONS SYSTEMS

RELATED APPLICATIONS

5

This application is related to U.S. Patent Application Serial No. _____
(attorney docket number E8699) entitled "Method of and Apparatus for Reducing the
Complexity of a Diversity Combining and Sequence Estimation Receiver", by Johan
Sköld and Per-Olof Eriksson, and filed concurrently herewith. This related application
10 is also assigned to the same assignee as the present application and is incorporated
herein by reference in its entirety.

FIELD OF THE INVENTION

15

The present invention relates generally to the demodulation of digitally
modulated radio signals received by a plurality of antennas and more specifically to the
diversity combining of radio signals subjected to multipath fading, time-dispersion and
interference.

20

BACKGROUND OF THE INVENTION

A common problem that occurs in the radio transmission of signals is that the
signals are sometimes lost as a result of multipath fading and interference which may
exist in a radio transmission channel. Throughout the following, the terms radio
25 transmission channel, radio channel, and channel are used equivalently to refer to the
same item. There are basically two multipath effects: flat fading and time dispersion.
Flat fading arises from the interaction of the transmitted signal, or main ray, and
reflections thereof, or echoes, which arrive at the receiver at approximately the same
time. If there are a large number of reflections, flat fading gives rise to a Rayleigh
30 distribution. Time dispersion occurs when the echoes are delayed with respect to the
main ray. There may also exist in the radio environment signal sources which are not
orthogonal to the desired signal. Non-orthogonal signals, or interference, often come
from radios operating on the same frequency (*i.e.*, co-channel interference) or from

radios operating on neighboring frequency bands (*i.e.*, adjacent-channel interference); non-orthogonal signal sources are referred to as interferers.

One known method of reducing the influence of Rayleigh fading is to use a receiver having two or more mutually separated antennas, for instance as described in
5 **Mobile Communications Design Fundamentals** by William C. Y. Lee, Howard W. Sams & Co., Indiana, USA. In section 3.5.1 of this book several examples are given describing how signals from two receiver amplifiers with separate antennas can be combined to counteract fading. These techniques are generally referred to as diversity combining.

10 Time dispersion may be advantageously corrected by using an equalizer. In the case of digital signal modulation, a maximum likelihood sequence estimation (MLSE) equalizer such as described in **Digital Communications**, 2nd Ed., by John G. Proakis, Mc-Graw Hill Book Company, New York, New York, USA, 1989 may be used. In section 6.7 of this book, various methods are described for detecting signals corrupted by time
15 dispersion, or inter-symbol interference (ISI), using MLSE equalization.

The impact of other signal interference may be reduced by employing array processing techniques with multiple antennas. For example, adaptive beamforming can be used to "steer" a null in the antenna pattern in the direction of an interferer.

Recently, methods have been proposed that partially solve the problems of
20 multipath fading and interference. In U.S. Patent 5,191,598 to Bäckström, *et al.*, for example, the problem of accurately detecting signals in the presence of flat fading and time dispersion is overcome by using a Viterbi-algorithm having a transmission function estimated for each antenna. By reference thereto, U.S. Patent 5,191,598 is incorporated herein in its entirety by reference.

25 A method of accurately detecting signals in the presence of flat fading and interference was presented in the *IEEE Transactions on Vehicular Technology*, Vol. 42, No. 4, Nov. 1993, J. H. Winters: "Signal Acquisition and Tracking with Adaptive Arrays in the Digital Mobile Radio System IS-54 with Flat Fading".

In a practical radio communication system, there commonly co-exists flat fading,
30 time dispersion, and interference. While the above-mentioned techniques address some of these problems, there exists a need to simultaneously and jointly combat flat fading, time dispersion, and interference.

Summary of the Invention

In view of the foregoing background, it is therefore an object of the present invention to jointly combat and correct for the simultaneous existence of flat fading, time dispersion, and interference.

A method is presented for generating and transmitting a signal representing a transmitted symbol sequence and receiving the signal on one or more antennas. The signal is processed to produce received signal samples for each of the antennas. Channel taps are estimated for each of the antennas. Impairment correlation properties are also estimated. Branch metrics are formed in a branch metric processor using the received signal samples and the channel tap and impairment correlation estimates. The branch metrics are employed in a sequence estimation algorithm to estimate the transmitted symbol sequence.

In one embodiment, branch metrics are formed by generating hypothetical symbol sequences and filtering the hypothetical signal sequences with the channel tap estimates to produce hypothesized received signal samples for each antenna. The hypothesized received signal samples are subtracted from the received signal samples to produce hypothesized error signals which are processed with the estimate of impairment correlation properties to produce branch metrics.

In another embodiment, an estimate of impairment correlation properties is formed by generating tentative detected symbol sequences which are filtered with the channel tap estimates to produce detected signal samples for each antenna. The detected signal samples are subtracted from the received signal samples to produce detected error signals which are processed with the estimate of impairment correlation properties to produce an update of the estimate of the impairment correlation properties.

In still another embodiment, branch metrics are performed by generating hypothetical symbol sequences and calculating pre-computed values for all of the hypothetical symbol sequences using the channel tap estimates and the estimates of impairment correlation properties. The pre-computed values are processed with the received signal samples to produce branch metrics.

In yet a further embodiment branch metrics are formed by generating hypothetical symbol sequences and combining the received signal samples with the

channel tap estimates and the estimate of impairment correlation properties to produce metric multipliers which are processed with the hypothetical symbol sequences to produce branch metrics.

5 An apparatus is also presented comprising a digital transmitter for generating and transmitting a signal representing a transmitted symbol sequence, a receiver for receiving said signal on one or more antennas, an analog to digital converter for converting the signal into received signal samples for each of the antennas, a channel tap estimator for estimating channel taps for each of the antennas to produce channel tap estimates, an impairment correlation estimator for estimating impairment correlation properties to produce an estimate of impairment correlation properties. The apparatus also comprises a branch metric processor coupled to the channel tap estimators, the impairment correlation estimator and the received signal samples for forming branch metrics using the received signal samples, the channel tap estimates, and the estimate of impairment correlation properties. The output of the branch metric processor is coupled to a sequence estimation processor which produces an estimate of said transmitted symbol sequence.

20 In another embodiment the branch metric processor comprises a symbol sequence generator for generating hypothetical symbol sequences coupled to a digital filter for filtering the hypothetical signal sequences with the channel tap estimates to produce hypothesized received signal samples for each antenna. The filters are coupled to means for subtracting said hypothesized received signal samples from the received signal samples to produce hypothesized error signals which are coupled to means for processing said hypothesized error signals with said estimate of impairment correlation properties to produce branch metrics.

25 Yet another embodiment is presented in which the impairment correlation estimator comprises a symbol sequence generator for generating tentative detected symbol sequences coupled to a digital filter for filtering the tentative detected symbol sequences with the channel tap estimates to produce detected signal samples for each antenna. The filter outputs are coupled to means for subtracting said detected signal samples from the received signal samples to produce detected error signals which are coupled to means for processing said detected error signals with said estimate of impairment correlation properties to produce an update of the estimate of impairment correlation properties.

These and other features and advantages of the present invention will be readily apparent to one of ordinary skill in the art from the following written description when read in conjunction with the drawings in which like reference numerals refer to like elements.

5

Brief Description of the Drawings

Figure 1 is a schematic illustration of a digital radio communication system;

Figure 2 is a schematic illustration of a receiver processor and transmission function
10 according to the present invention;

Figure 3 is a schematic illustration of a transmission function;

Figure 4 is a schematic illustration of a branch metric processor according to the
15 present invention;

Figure 5 is a schematic illustration of an adaptive estimator of the impairment correlation properties;

Figure 6 is a schematic illustration of yet another embodiment of a branch metric processor according to the present invention;

Figure 7 is a schematic illustration of another embodiment of a receiver processor and a transmission function according to the present invention; and
25

Figure 8 is a schematic illustration of yet another embodiment of a receiver processor and a transmission function according to the present invention.

DESCRIPTION OF THE INVENTION

30

In the following description, for purposes of explanation and not limitation, specific details are set forth, such as particular circuits, circuit components, techniques,

etc. In order to provide a thorough understanding of the invention. However It will be apparent to one of ordinary skill in the art that the present invention may be practiced in other embodiments that depart from these specific details. In other instances, detailed descriptions of well-known methods, devices, and circuits are omitted so as not to
5 obscure the description of the present invention with unnecessary detail.

A radio transmitter and receiver system for a radio communication system is illustrated schematically in Figure 1. The radio communication system may operate using frequency division multiple access (FDMA), time division multiple access (TDMA), or code division multiple access (CDMA), or some combination thereof. A transmitter
10 has a digital symbol generator 102 which receives an information carrying signal 101 and generates a corresponding digital symbol sequence, S . The symbols S are subjected to digital to analog (D/A) conversion, modulation, pulse shape filtering, amplification, and are transmitted as analog signal Y by digital transmitter 103 according to known techniques.

15 In addition to thermal noise, there may also exist an interferer 108 transmitting signal X which may be non-orthogonal to signal Y . Signals Y and X travel through separate radio channels and are intercepted by antennas 104 which are D in number.

Radio units 105 amplify, downconvert, and filter the received signals according to known methods to produce analog signals. Each analog signal is coupled to an
20 analog-to-digital (A/D) converter 106, which converts the analog signal into a received signal sample stream $r_d(kT_s)$, where T_s is the sample period, the reference numeral k is an integer counter, and the subscript d indicates that the signal arrives from the d^{th} antenna $1 \leq d \leq D$. The sampling period T_s may be less than the symbol period T . The received signal sample streams are collected in processor 107, which processes these
25 streams to produce an estimate of the transmitted digital symbol stream, \hat{S} . In later descriptions, transmission function 109 is used to refer to the signal path through digital transmitter 103, the radio transmission channel (not shown in Figure 1), antennas 104, radio units 105 and A/Ds 106 collectively.

The processing unit 107 is illustrated in greater detail in Figure 2 where, for
30 simplicity, the number D of antennas is restricted to three: designated a , b , and c . Processing unit 107 may be, for example, a Digital Signal Processor (DSP) such as a TMS320C50 manufactured by Texas Instruments. The function of processing unit 107

is to produce an estimate of the transmitted digital symbol stream \hat{S} which accurately corresponds to the symbol sequence S which was originally transmitted.

Transmission function 109 produces the received signal sample streams $r_a(kT_s)$, $r_b(kT_s)$, and $r_c(kT_s)$ which are sent to processing unit 107 where they are processed in accordance with the present invention. The received signal sample streams $r_a(kT_s)$, $r_b(kT_s)$, and $r_c(kT_s)$ are coupled to a signal pre-processor, or sync, block 206 where the received signal sample streams are correlated with known timing/synchronization sequences as described, for example, by Giovanna, *et al.* "Fast Adaptive Equalizers for Narrow-Band TDMA Mobile Radio", *IEEE Transactions on Vehicular Technology*, Vol. 40, No. 2, May 1991, pp. 392-404. For the case of symbol-spaced demodulation, if the sample period T_s is less than symbol period, T , the signal pre-processor 206 performs a decimation of the received signal sample streams $r_a(kT_s)$, $r_b(kT_s)$, and $r_c(kT_s)$ to produce one sample per symbol: designated $r_a(n)$, $r_b(n)$, and $r_c(n)$ respectively. For the case of fractionally-spaced demodulation, more than one sample per symbol is generated.

Estimating circuits 202a, 202c, and 202e produce channel tap estimates $c_a(\tau)$, $c_b(\tau)$, and $c_c(\tau)$ which are used to model the radio transmission channel associated with each particular antenna. Initial channel tap estimates can be obtained from sync correlation values or least-squares estimation according to known techniques. If the channel must be tracked, it is typical to use received data and tentative symbol estimate values generated in the sequence estimation processor 204. Channel tracking is known to those skilled in the art as discussed, for example, in **Digital Communications 2nd Ed.** by Proakis as previously mentioned, and by A. P. Clark and S. Hariharan, "Adaptive Channel Estimates for an HF Radio Link", *IEEE Trans. on Communications*, vol. 37, pp. 918-926, Sept. 1989. The channel tap estimates $c_a(\tau)$, $c_b(\tau)$, and $c_c(\tau)$ are coupled to the input of the branch metric processor 203.

Also coupled to the branch metric processor 203 is an estimate of the impairment correlation properties obtained from impairment correlation estimator 207. The estimate of the impairment correlation properties comprises information regarding the impairment correlation properties between the antennas 104, or between relative sample phases as will be discussed in greater detail hereinafter. The impairment correlation estimator uses impairment process estimates to update and possibly track

the estimate of the impairment correlation properties which is discussed in further detail in the ensuing text and figures.

Branch metric processor 203 uses received signal samples $r_a(n)$, $r_b(n)$, and $r_c(n)$, channel tap estimates $c_a(\tau)$, $c_b(\tau)$, and $c_c(\tau)$, and the estimate of the impairment correlation properties to form branch metric $M_h(n)$. This branch metric is used, for example, in a sequence estimation processor 204 to develop tentative and final estimates of the transmitted symbols.

It will be appreciated by one of ordinary skill in the art how the present invention operates when fractionally-spaced (T/M) equalization is employed. In this case, each signal preprocessor 206 produces M samples per symbol period, which correspond to M different sampling phases. This gives rise to M received signal sample streams per antenna. As a result, branch metric processor 203 receives D times M sample streams. As before, the channel tap estimators 202a - 202c produce channel tap estimates for antennas a - c respectively. However, these channel tap estimates are more in number, as estimates for each sampling phase must be provided. Also, the impairment correlation estimator 207 estimates impairment correlation properties over antennas and sampling phases. This is done by treating the D antennas and M sampling phases as D times M antennas. As a result, the branch metric processor operates in a manner equivalent to having D times M antennas and one sample per symbol. It is apparent that the present invention can be applied to the case of one receive antenna and fractionally-spaced equalization.

The transmission function 109 is illustrated in greater detail in Figure 3 where, for simplicity, the number of interferers is restricted to one. It is obvious to one skilled in the art that the present invention may also be used for the case where there are two or more interferers. The transmit function 109 begins with the signal path for the symbol sequence S through digital transmitter 103 which transmits analog signal Y. The analog signal Y propagates through a separate radio transmission channel to each of the three receiver antennas: radio channel 301a to receiver antenna 104a, radio channel 301b to receiver antenna 104b, and radio channel 301c to receiver antenna 104c. Similarly, interference signal X also propagates through three other separate radio channels 302a-302c to receiver antennas 104a-104c respectively. Radio channels 301a-301c and 302a-302c may introduce fading and time dispersion. Omnipresent thermal noise

processes $n_a - n_c$ are also received by receiver antennas 104a-104c respectively. Each antenna 104a-104c is coupled to a radio unit 105a-105c respectively which amplifies, downconverts, and filters the received signals according to known methods to produce an analog signal. Each analog signal is coupled to an analog-to-digital (A/D) converter
5 106a-106c which converts the analog signals into received signal sample streams $r_a(kT_s)$, $r_b(kT_s)$, and $r_c(kT_s)$. One method for conversion from analog to digital is to use log-polar signal processing, as described in U. S. Patent 5,048,059 to Dent incorporated by reference herein in its entirety. For subsequent processing, a conversion from log-polar to rectangular samples is made, so that, for example, I and
10 Q samples, sometimes referred to as complex samples, are used. By using log-polar signal processing initially, a limiting receiver which provides signal strength and phase samples can be used, and adaptive gain control can be made simple.

In an MLSE equalizer, all possible transmitted symbol sequences S are considered. In one implementation, hypothesized symbol values $s_h(n)$ are filtered by
15 channel tap estimates $c_a(\tau)$, $c_b(\tau)$, and $c_c(\tau)$ to produce hypothesized received samples $r_{a,h}(n)$, $r_{b,h}(n)$, and $r_{c,h}(n)$ for each antenna. The differences between the hypothesized $r_{a,h}(n)-r_{c,h}(n)$ and the actual $r_a(n)-r_c(n)$ received signal sample streams, referred to as the hypothesis errors, give an indication of how good a particular hypothesis is. The squared magnitude of the hypothesis error is used as a metric to evaluate a particular
20 hypothesis. The metric is accumulated for different hypotheses for use in determining which hypotheses are better using the sequence estimation algorithm. This process may be efficiently realized using the Viterbi algorithm, which is a known form of dynamic programming. A description of the Viterbi algorithm may be found in Forney, G., "The Viterbi Algorithm", *Proc. of the IEEE*, vol. 61, pp. 268-278, March, 1973. As is
25 obvious to one of ordinary skill in the art, other sequence estimation algorithms, such as the M-algorithm, may also be used.

In an MLSE equalizer, there are states associated with different symbol sequence hypotheses $s_h(n)$. At a given iteration, there are previous states: each associated with an accumulated metric. Each pairing of a previous state with a current
30 state results in a branch metric, $M_h(n)$. The candidate metric for a current state is then the sum of the branch metric $M_h(n)$ and the previously accumulated metric. For each current state, the previous state which gives the smallest candidate metric is selected as the predecessor state, and the smallest candidate metric becomes the accumulated

metric for the current state. For metric combining, as described in aforementioned U.S. Patent 5,191,598, the branch metric can be expressed as:

$$M_h(n) = [r(n) - C s_h(n)]^H D [r(n) - C s_h(n)]$$

where:

$$r(n) = [r_a(n) r_b(n) r_c(n)]$$

$$C = \begin{bmatrix} c_a(0) & \dots & c_a(N_t - 1) \\ c_b(0) & \dots & c_b(N_t - 1) \\ c_c(0) & \dots & c_c(N_t - 1) \end{bmatrix}$$

$$s_h(n) = [s_h(n) s_h(n-1) \dots]^T$$

$$D = \begin{bmatrix} K_a & 0 & 0 \\ 0 & K_b & 0 \\ 0 & 0 & K_c \end{bmatrix}$$

The channel tap estimates for each signal received on antenna 104a-104c are designated by $c_a(\tau)$, $c_b(\tau)$, $c_c(\tau)$ respectively where τ is the delay (i.e. $\tau = 0$ is the main ray, $\tau = 1$ is the first echo, etc.). N_t is the number of channel taps estimated per antenna and K_a , K_b , K_c are weighting coefficients for antennas 104a-104c respectively.

The present invention takes advantage of the fact that, from a diversity and equalization point-of-view, the impairment (interference + noise) on multiple receive antennas 104 is often correlated. By expanding diversity combining techniques to exploit this correlation, significant gains are realized. For optimal performance, a whitening, or decorrelation, process may be applied and the optimum branch metric may include the inverse of the impairment correlation matrix. The optimum branch metric $M_h(n)$ according to the present invention is:

$$M_n(n) = [r(n) - C(n)s_n(n)]^H A(n) [r(n) - C(n)s_n(n)] = e_n^H(n) A(n) e_n(n)$$

where:

$$A(n) = R_{zz}(n)^{-1}, \text{ or a related quantity; } R_{zz}(n) = E(z(n)z^H(n))$$

$$z(n) = [z_a(n)z_b(n)z_c(n)]^T; \quad e_n(n) = r(n) - C(n)s_n(n)$$

The time varying nature of the channel and the impairment correlation are denoted with time index n . The $R_{zz}(n)$ matrix is referred to as the impairment correlation matrix at discrete time, n . The $A(n)$ matrix (*i.e.*, the A-matrix) is the inverse of the $R_{zz}(n)$ matrix, or
 5 a related quantity such as the adjoint or pseudo-inverse. As is obvious to one of ordinary skill in the art, $R_{zz}(n)$ and $A(n)$ are specific examples of impairment correlation properties of which other forms are known. Throughout the following, the term A-matrix is used generically to refer to any estimate of the impairment correlation properties.

The impairments on antennas 104a-104c at time n are designated by $z_a(n)$,
 10 $z_b(n)$, and $z_c(n)$ respectively. For a given hypothesis, $e_n(n)$ is an estimate of the impairment process. As shown above, the A-matrix, $A(n)$, is the inverse of the impairment correlation matrix $R_{zz}(n)$. For the case of uncorrelated impairment (*i.e.*, no interferer) the A-matrix reduces to diagonal matrix D . When the signal is known or detected correctly, the impairment is given by:

$$z(n) = r(n) - C(n)s_{\text{det}}(n)$$

15

where:

$$s_{\text{det}}(n) = [s_{\text{det}}(n)s_{\text{det}}(n-1)\dots]^T$$

Note that $s_{\text{det}}(n)$ is the known or detected symbol sequence at time n .

Determination of the A-matrix for use in the present invention can be performed in a number of ways depending upon the specific application and the required performance. The simplest approach is to use a fixed set of values for the A-matrix,
 20 stored in memory, that are never updated. These values depend primarily on the configuration of the receive antennas and on the carrier frequencies being employed. An alternative approach is to determine the A-matrix from synchronization information

and to keep the A-matrix values constant between synchronization, or other, known fields. At each new occurrence of the synchronization field, the A-matrix can be recomputed, with or without use of the previous A-matrix values. Another alternative approach is to use synchronization fields to initialize, or improve, the A-matrix values
 5 and then to use decisions made on the data field symbols to track the A-matrix values.

Also, consideration is given for the method used to track the A-matrix values. Since the A-matrix comprises information regarding the impairment correlation properties standard estimation methods for estimating correlation or inverse correlation matrices can be applied. Using either known or detected symbol values, impairment
 10 values can be obtained by taking the differences between the received signal sample streams $r_a(n)-r_c(n)$ and the hypothesized received signal sample streams $r_{a,h}(n)-r_{c,h}(n)$. At time n , this gives a vector of impairment values, denoted $z(n)$; one value for each antenna. A straightforward way of forming the A-matrix is given by:

$$R(n) = \lambda R(n-1) + K z(n) z^H(n)$$

$$A(n) = R^{-1}(n)$$

15 K is a scaling constant, typically 1 or $\sqrt{(1-\lambda)}$. Because $R(n)$ is a Hermitian matrix, only a portion of the matrix elements need be computed.

Such a straightforward approach is fairly high in complexity. One way to reduce complexity is to apply the matrix inversion lemma and update the A-matrix directly as:

$$A(n) = \frac{1}{\lambda} \left[A(n-1) - \left(\frac{1}{\lambda + z(n)^H p(n)} \right) p(n) p^H(n) \right]$$

where:

$$p(n) = A(n-1) z(n)$$

20 Because the A-matrix is Hermitian, it is only necessary to compute those elements on the diagonal and either those elements above or below the diagonal.

These techniques for estimating and tracking the A-matrix are given only for purposes of illustration. In general, the A-matrix can be expressed and estimated in a variety of ways, as is obvious to one of ordinary skill in the art. See, for example, the
 25 book by S. Haykin, **Adaptive Filter Theory, Second Edition**, Prentice-Hall, Englewood Cliffs, N.J., 1991. The present invention may also be applied to the blind equalization

problem in which known synchronization sequences are absent. In this case, the A-matrix is estimated in a manner similar to how the channel is estimated.

For the purposes of illustration, the present invention will now be described in greater detail as exemplified in four different embodiments.

5

Description of Embodiment having a Symbol-Spaced Equalizer with Two Antennas and Adaptive Channel Estimates

10

In a first embodiment, a processor 107 having a symbol-spaced (i.e., T-spaced) equalizer is presented where the channel must be tracked over the data field, or burst. This embodiment is applicable to the digital cellular system defined by the IS-54B specification which has relatively long TDMA data bursts, or time slots, (6.67
15 milliseconds) with respect to time. For this embodiment, the branch metric processor 203 is illustrated in greater detail in Figure 4 where, for simplicity, the number of antennas is further restricted to two: designated a and b. This particular embodiment has usefulness in that the use of two receive antennas is common in many cellular systems which already employ some form of diversity combining. As before, it is
20 obvious to one of ordinary skill in the art that this embodiment may also be employed in the case where there are three or more antennas.

The impairment correlation matrix R_{xx} and the inverse impairment correlation matrix A are defined as follows:

$$R_{xx} = P = \begin{bmatrix} p_{aa} & p_{ab} \\ p_{ab}^* & p_{bb} \end{bmatrix}$$

$$R_{xx}^{-1} = \frac{1}{(p_{aa}p_{bb} - |p_{ab}|^2)} \begin{bmatrix} p_{bb} & -p_{ab} \\ -p_{ab}^* & p_{aa} \end{bmatrix} = W \begin{bmatrix} p_{bb} & -p_{ab} \\ -p_{ab}^* & p_{aa} \end{bmatrix} = A$$

25 The variable p_{aa} denotes the impairment power received on antenna a; the variable p_{bb} denotes the impairment power received on antenna b. The off-diagonal matrix elements are the cross correlation values: p_{ab} denotes the correlation of the impairment received on antenna a with the conjugate of that received on antenna b.

The branch metric then becomes:

$$M_h(n) = \mathbf{e}_h(n)^H \mathbf{A}(n) \mathbf{e}_h(n) = w \left[p_{bb} |\mathbf{e}_{a,h}(n)|^2 - 2 \operatorname{Re} \{ p_{ab} \mathbf{e}_{a,h}(n) \cdot \mathbf{e}_{b,h}(n) \} + p_{aa} |\mathbf{e}_{b,h}(n)|^2 \right]$$

where:

$$w = \frac{1}{p_{aa} p_{bb} - |p_{ab}|^2} \quad \text{and} \quad \mathbf{e}_{a,h}(n) = r_a(n) - r_{a,h}(n)$$

The calculation of this branch metric is schematically illustrated in Figure 4.

A symbol sequence generator 410 generates hypothesized symbol sequences $\mathbf{s}_h(n)$. These sequences are filtered in filters 400 using channel tap estimates $c_a(\tau)$ and $c_b(\tau)$ for antennas a and b to produce hypothesized received signal samples $r_{a,h}(n)$ and $r_{b,h}(n)$, respectively. The hypothesized received signal samples, $r_{a,h}(n)$, are subtracted from the actual received signal samples from antenna a, $r_a(n)$, in summing junction 401 to produce error signals $\mathbf{e}_{a,h}(n)$. Similarly hypothesized received signal samples, $r_{b,h}(n)$, are subtracted from the actual received signal samples from antenna b, $r_b(n)$, in summing junction 402 to produce error signals $\mathbf{e}_{b,h}(n)$. Blocks 403 form the squared magnitudes of the error signals $\mathbf{e}_{a,h}(n)$ and $\mathbf{e}_{b,h}(n)$. The squared magnitude for error signals $\mathbf{e}_{a,h}(n)$ is multiplied at junction 406 by multiplier m_{aa} , the result being coupled to summing junction 408. The squared magnitude for error signals $\mathbf{e}_{b,h}(n)$ are multiplied at junction 407 by multiplier m_{bb} , the result being coupled to summing junction 408. Finally, multiplier 404 forms the product of $\mathbf{e}_{a,h}(n)$ and $\mathbf{e}_{b,h}^*(n)$, the product of which is subsequently multiplied by multiplier m_{ab} in multiplier 405, forming the real part only. The result is subtracted in summing junction 408, the output of which is the branch metric $M_h(n)$. The multipliers m_{aa} , m_{bb} , and m_{ab} are related to the impairment correlation matrix by:

$$m_{aa} = w p_{bb}$$

$$m_{bb} = w p_{aa}$$

$$m_{ab} = 2w p_{ab}$$

As is obvious to one skilled in the art the w term is common to the branch metric calculation and may be applied in a different manner or even omitted when the denominator to w approaches zero.

At time n , the A matrix elements are updated as:

$$p_{aa}(n+1) = \lambda p_{aa}(n) + |e_a(n)|^2 K$$

$$p_{ab}(n+1) = \lambda p_{ab}(n) + e_a(n) e_b^*(n) K$$

$$p_{bb}(n+1) = \lambda p_{bb}(n) + |e_b(n)|^2 K$$

K is a scaling factor which, if equal to unity, is dropped from the calculation to reduce the number of computations. K may be derived from λ which is the so-called "forgetting factor".

A schematic illustration of the impairment correlation matrix update is shown in Figure 5. Tentative detected symbol values $s_{det}(n)$ from sequence estimation processor 204 are filtered in filters 500 using channel tap estimates $c_a(\tau)$ and $c_b(\tau)$ from channel tap estimators 202 for antennas a and b to produce expected received samples $r_{a,det}(n)$ and $r_{b,det}(n)$, respectively. Impairment signal $z_a(n)$ is produced by subtracting, in summing junction 501 $r_{a,det}(n)$ from the actual received signal samples from antenna a, $r_a(n)$. Similarly, impairment signal $z_b(n)$ is produced by subtracting, in summing junction 502 $r_{b,det}(n)$ from the actual received signal samples on antenna b, $r_b(n)$. If the tentative detected symbol values are correct and the channel tap estimates are accurate, then error signals $z_a(n)$ and $z_b(n)$ represent the impairment received on antennas a and b respectively. Impairment signals $z_a(n)$ and $z_b(n)$ are scaled by the root of the scaling factor K in multipliers 503 and 505 respectively to produce scaled impairment signals which are coupled to blocks 506 and 507, respectively.

The impairment power received on antenna a, $p_{aa}(n)$, is multiplied in multiplier 511 by the forgetting factor, λ , and summed in junction 510 with the squared magnitude of the scaled impairment signal from block 506 to produce the updated impairment power $p_{aa}(n+1)$. The value of $p_{aa}(n+1)$ is then used to overwrite the memory location 515 of the previous impairment power $p_{aa}(n)$. Similarly, the previous impairment power received on antenna b, $p_{bb}(n)$, is multiplied in multiplier 513 by the forgetting factor, λ , and summed in junction 512 with the squared magnitude of the scaled error signal from block 507 to produce the updated impairment power $p_{bb}(n+1)$ which is used to overwrite the memory location 514 of the previous impairment power $p_{bb}(n)$. To produce the updated impairment cross correlation, the scaled error signal from multiplier 503 is

multiplied with the conjugate of the scaled error signal from multiplier 505 in junction 504. Also, the previous cross-correlation $p_{ab}(n)$, stored in memory 516, is scaled by the forgetting factor in multiplier 509. The output of junction 504 is summed in junction 508 with the output of multiplier 509 to yield the updated cross correlation $p_{ab}(n+1)$. As before, the updated value $p_{ab}(n+1)$ is used to overwrite the memory location 516 of the previous value $p_{ab}(n)$.

There is typically a delay in updating the channel tap estimates which allows the tentative detected symbols to become reliable. In U.S. patent 5,164,961 by Gudmundson, *et al.*, incorporated herein by reference in its entirety, this delay is avoided by using multiple channel models: one for each state in the sequence estimation processor 204. With the present invention, there is also a delay in updating the A-matrix quantities. It is obvious to one of ordinary skill in the art that this delay can be avoided by using multiple A-matrices; one for each state in the sequence estimation processor 204.

15

Description of Embodiment having a Symbol-Spaced Equalizer with Two Antennas and Fixed Channel Estimates

In a second embodiment a receiver having a symbol-spaced equalizer is presented where the channel can be considered static over a TDMA burst. This embodiment is applicable to the digital cellular system defined by the pan-European GSM specification which has relatively short (577 microseconds) TDMA data fields with respect to time. In this case, the impairment correlation matrix R_{xx} , and hence the A-matrix, do not vary over the burst and can be estimated from the sync word embedded in the GSM frame. In this instance, the branch metric can be expressed as:

25

$$M_h(n) = [r(n) - Cs_h(n)]^H A(r(n) - Cs_h(n))$$

$$M_h(n) = r^H(n) Ar(n) - 2\text{Re}\{s_h(n)^H C^H Ar(n)\} + s_h(n)^H C^H A C s_h(n)$$

Referring now to Figure 6, processing time is saved by pre-computing and storing in memory 601 the following values for all possible hypothetical symbol sequences, s_h :

$$f_h = 2 A^H C s_h$$

$$g_h = s_h^H C^H A C s_h$$

Using these pre-computed values, the branch metric may be simplified as:

$$M_h(n) = -\text{Re}\{f_h^H r(n)\} + g_h$$

where:

$$r(n) = [r_a(n) r_b(n)]^T$$

For each hypothesized symbol sequence $s_h(n)$, the received signal samples $r_a(n)$ and $r_b(n)$ are multiplied in blocks 602 and 603, respectively, by the corresponding f_h value, which was precomputed as described above and retrieved from memory 601; only the real parts of the products are formed. The h-index refers to the hypothesis index which relates a particular f_h value to a particular hypothesized symbol sequence $s_h(n)$. The output of multipliers 602 and 603 are coupled to summing junction 604 where they are summed and the results passed to junction 605 where the output of junction 604 is subtracted from the corresponding g_h value: also precomputed as described above and retrieved from memory 601. The result is the branch metric $M_h(n)$.

15 Description of Embodiment having a Fractionally-Spaced Equalizer with one or more Antennas and Adaptive Channel Estimates with Partial Optimization

In a further embodiment a receiver having one or more antennas coupled to a processor 107 comprising a fractionally-spaced (T/M) equalizer with adaptive channel tracking is presented. This particular embodiment is applicable to the digital cellular system defined by the IS-54B specification which has relatively long (6.67 milliseconds) time slots, or bursts, such that the channel tap estimates need to be updated during the duration of the burst. For this embodiment, receiver processor 107 is illustrated in greater detail in Figure 7 where, for simplicity, only a single interferer X and three antennas designated a, b, c are considered and $M=2$. It is obvious to one of ordinary skill in the art that the present invention may be practiced with a plurality of interferers and a plurality of antennas and a fractional spacing other than $M=2$. The transmission

function 109 shown in Figure 7 is, for example, identical to that described by Figure 3 which produces three received signal sample streams: $r_a(kT_s)$, $r_b(kT_s)$ and $r_c(kT_s)$. The received signal sample streams: $r_a(kT_s)$ - $r_c(kT_s)$ are each coupled to a signal preprocessor 707 which performs correlations with a known synchronization pattern similar to that described for block 206 of Figure 2. Timing is determined from the correlation values using some optimization criterion, such as maximum energy in the channel taps. In this particular embodiment, since M has been chosen equal to 2, each signal pre-processor 707 produces, from each incoming received signal sample stream, two samples per symbol. For example, as shown in Figure 7, $r_{a,0}(n)$, $r_{a,1}(n)$ are generated from received signal sample stream $r_a(kT_s)$. Similarly $r_{b,0}(n)$, $r_{b,1}(n)$ and $r_{c,0}(n)$, $r_{c,1}(n)$ are produced from received signal sample streams $r_b(kT_s)$ and $r_c(kT_s)$ respectively. If, for example, M is chosen to be equal to 4 then 4 samples per symbol would be produced. These signals, $r_{a,0}(n)$, $r_{a,1}(n)$, $r_{b,0}(n)$, $r_{b,1}(n)$, $r_{c,0}(n)$, and $r_{c,1}(n)$, are coupled to the branch metric preprocessor 701 where they are treated as though each signal, $r_{a,0}(n)$, $r_{a,1}(n)$, $r_{b,0}(n)$, $r_{b,1}(n)$, $r_{c,0}(n)$, and $r_{c,1}(n)$, arrived from a separate antenna.

In practice, one can expand the expression for the branch metric and collect computations to provide a lower complexity implementation. Two techniques can be used to reduce complexity: a) expand the branch metric expression and collect like terms, and b) reorder at which iterations certain terms are computed. Using the first technique, metric multipliers, which can be pre-computed for all hypotheses, are expressed as:

$$e(j,n) = c^H(j,n) A(n) r(n)$$

$$f(j,n) = c^H(j,n) A(n) c(j,n)$$

$$g(j,k,n) = c^H(j,n) A(n) c(k,n) \quad \text{where } k > j$$

where $c(j,n)$ is the j th column of $C(n)$. J is the number of channel taps. In other words, the received signal vector $r(n)$ is modeled as:

$$r(n) = \sum_{j=0}^J s_h(n-j) c(j,n)$$

The values $e(j,n)$, $f(j,n)$, and $g(j,k,n)$ are computed by the branch metric preprocessor 701 and stored in memory (not shown). The indices j and k are ray indices. The values

$e(j,n)$, $f(j,n)$, and $g(j,k,n)$ are referred to as metric multipliers since they can be used in multiplications to form the equalizer metrics in branch metric processor 704. The values $e(j,n)$, $f(j,n)$, and $g(j,k,n)$ are coupled to branch metric processor 704 which computes the branch metric $M_n(n)$ according to:

$$M_n(n) = - \sum_{j=0}^{J-1} 2 \operatorname{Re} \{ e(j,n) s_n^*(n-j) \} + \sum_{j=0}^{J-1} f(j,n) |s_n(n-j)|^2$$

$$+ 2 \sum_{j=0}^{J-1} \sum_{k=j+1}^{J-1} \operatorname{Re} \{ g(j,k,n) s_n^*(n-j) s_n(n-k) \}$$

In systems where all symbols have the same amplitude, such as binary phase shift keying (BPSK) and quaternary phase shift keying (QPSK) systems, the term $|s_n(n-j)|^2$ is a constant, independent of hypothesis. Thus, this term can be dropped, obviating the need to compute and use the $f(j,n)$ metric multipliers.

While the embodiment was illustrated for the case of three antennas, it is obvious to one of ordinary skill in the art that the present invention may be practiced with a single antenna and fractionally-spaced equalization.

Description of Embodiment having a Fractionally-Spaced Equalizer with one or more Antennas and Adaptive Channel Estimates with Full Optimization

A further reduction in complexity can be achieved by employing the receiver processor 107 shown in Figure 8. The receiver processor 107 of Figure 8 is essentially identical to that of Figure 7 with the difference being the branch metric preprocessor 801 and the branch metric processor 804. As shown in Figure 8, branch metric preprocessor 801 pre-computes and stores in memory (not shown) the following alternate metric multipliers:

$$Z(n) = \sum_j c^H(j, n+j) A(n+j) r(n+j)$$

$$S(k,n) = \sum_j c^H(j, n+j) A(n+j) c(j+k, n+j)$$

In practice, it may be advantageous to approximate $A(n+j)$ with $A(n)$ and $c(j, n+j)$, $c(j+k, n+j)$ with $c(j, n)$, $c(j+k, n)$ respectively. Alternate metric multipliers $Z(n)$ and $S(k,n)$

are coupled to branch metric processor 804 which computes the branch metric according to:

$$M_n(n) = \text{Re} \left\{ s_n^*(n) \left[2Z(n) + s_n(n)S(0,n) + \sum_{k=1} 2S(k,n)s_n(n-k) \right] \right\}$$

While the embodiment was illustrated for the case of three antennas, it is obvious to one of ordinary skill in the art that the present invention may be practiced with a single antenna and fractionally-spaced equalization. While the present invention has further been described with respect to a particular digital cellular communications system, those skilled in the art will recognize that the present invention is also applicable to other communications systems and that therefore the present invention is not limited to the specific embodiments described and illustrated herein. Different embodiments and adaptations besides those shown and described as well as many variations, modifications and equivalent arrangements will now be reasonably suggested by the foregoing specification and drawings without departing from the substance or scope of the invention. While the present invention has been described herein in detail in relation to its preferred embodiments, it is to be understood that this disclosure is only illustrative and exemplary of the present invention and is merely for the purposes of providing a full and enabling disclosure of the invention. Accordingly, it is intended that the invention be limited only by the spirit and scope of the claims appended hereto.

What is claimed is:

- 1 1. A method for reducing the effects of signal fading, time dispersion, and interference
2 in a radio communications system, comprising the steps of:
3 (a) generating and transmitting a signal representing a transmitted symbol
4 sequence;
5 (b) receiving said signal on at least two separate antennas;
6 (c) processing said signal to produce received signal samples for each of said
7 antennas;
8 (d) estimating channel taps for each of said antennas to produce channel tap
9 estimates;
10 (e) estimating impairment correlation properties to produce an estimate of
11 impairment correlation properties;
12 (f) forming branch metrics in a branch metric processor using said received
13 signal samples, said channel tap estimates, and said estimate of impairment correlation
14 properties; and
15 (g) employing said branch metrics in a sequence estimation algorithm to
16 estimate said transmitted symbol sequence.
- 1 2. A method according to claim 1, in which processing step (c) employs log-polar signal
2 processing.
- 1 3. A method according to claim 1, in which said estimate of impairment correlation
2 properties is represented as the inverse of an impairment correlation matrix.

- 1 4. A method according to claim 1, in which said forming step (f) comprises:
2 (a) generating hypothetical symbol sequences;
3 (b) filtering said hypothetical signal sequences with said channel tap estimates
4 to produce hypothesized received signal samples for each antenna;
5 (c) subtracting said hypothesized received signal samples from the received
6 signal samples to produce hypothesized error signals; and
7 (d) processing said hypothesized error signals with said estimate of impairment
8 correlation properties to produce branch metrics.
- 1 5. A method according to claim 1, in which said estimating step (e) comprises:
2 (a) generating tentative detected symbol sequences;
3 (b) filtering said tentative detected symbol sequences with said channel tap
4 estimates to produce detected signal samples for each antenna;
5 (c) subtracting said detected signal samples from the received signal samples to
6 produce detected error signals; and
7 (d) processing said detected error signals with said estimate of impairment
8 correlation properties to produce an updated estimate of said impairment correlation
9 properties.
- 1 6. The method of claim 1, in which said forming step (f) comprises:
2 a) generating hypothetical symbol sequences;
3 b) calculating pre-computed values for all of said hypothetical symbol
4 sequences using said channel tap estimates and said estimate of impairment
5 correlation properties; and
6 c) processing said received signal samples with said pre-computed values to
7 produce branch metrics.

- 1 7. A method according to claim 1, in which said forming step (f) comprises:
2 a) generating hypothetical symbol sequences;
3 b) combining the received signal samples with channel tap estimates and said
4 estimate of impairment correlation properties to produce metric multipliers $e(j,n)$;
5 c) combining said channel tap estimates with one another and said estimate of
6 impairment correlation properties to produce metric multipliers $f(j,n)$ and $g(j,k,n)$; and
7 d) combining said metric premultipliers with said hypothetical symbol sequences
8 to produce branch metrics.
- 1 8. A method according to claim 1, in which said forming step (f) comprises:
2 a) generating hypothetical symbol sequences;
3 b) combining the received signal samples with channel tap estimates and said
4 estimate of impairment correlation properties to produce metric multipliers $e(j,n)$;
5 c) combining said channel tap estimates with one another and said estimate of
6 impairment correlation properties to produce metric multipliers $g(j,k,n)$; and
7 d) combining said metric premultipliers with said hypothetical symbol sequences
8 to produce branch metrics.
9
- 1 9. The method of claim 1, in which said employing step (g) further comprises the use of
2 the Viterbi algorithm.
- 1 10. A method according to claim 1, in which said forming step (f) comprises:
2 a) generating hypothetical symbol sequences;
3 b) combining said received signal samples with said channel tap estimates and
4 said estimate of impairment correlation properties to produce $Z(n)$ values;
5 (b) combining said channel tap estimates with one another and said estimate of
6 impairment correlation properties to produce $S(k,n)$ values; and
7 (c) combining said $Z(n)$ and $S(k,n)$ values with said hypothetical symbol
8 sequences to produce branch metrics.

- 1 11. An apparatus for reducing the effects of signal fading, time dispersion, and
2 interference in a radio communications system, comprising:
3 a digital transmitter for generating and transmitting a signal representing a
4 transmitted symbol sequence;
5 a receiver for receiving said signal on at least two separate antennas;
6 an analog to digital converter for converting said signal into received signal
7 samples for each of said antennas;
8 a channel tap estimator for estimating channel taps for each of said antennas to
9 produce channel tap estimates;
10 an impairment correlation estimator for estimating impairment correlation
11 properties to produce an estimate of impairment correlation properties;
12 a branch metric processor for forming branch metrics using said received signal
13 samples, said channel tap estimates, and said estimate of impairment correlation
14 properties; and
15 a sequence estimation processor employing said branch metrics to estimate
16 said transmitted symbol sequence.
- 1 12. The apparatus of claim 11, in which said analog to digital converter employs log-
2 polar signal processing.
- 1 13. The apparatus of claim 11, in which said branch metric processor comprises:
2 a symbol sequence generator for generating hypothetical symbol sequences;
3 means for filtering said hypothetical signal sequences with said channel tap
4 estimates to produce hypothesized received signal samples for each antenna;
5 means for subtracting said hypothesized received signal samples from the
6 received signal samples to produce hypothesized error signals; and
7 means for processing said hypothesized error signals with said estimate of
8 impairment correlation properties to produce branch metrics.

1 14. The apparatus of claim 11, in which said impairment correlation estimator
2 comprises:
3 a symbol sequence generator for generating tentative detected symbol
4 sequences;
5 a digital filter for filtering said tentative detected symbol sequences with said
6 channel tap estimates to produce detected signal samples for each antenna;
7 means for subtracting said detected signal samples from the received signal
8 samples to produce detected error signals; and
9 means for processing said detected error signals with said estimate of
10 impairment correlation properties to produce an update of the estimate the impairment
11 correlation properties.

1 15. The apparatus of claim 11, in which said branch metric processor comprises:
2 a symbol sequence generator for generating hypothetical symbol sequences;
3 means for calculating pre-computed values for all of said hypothetical symbol
4 sequences using said channel tap estimates and said estimate of impairment
5 correlation properties; and
6 means for processing said received signal samples with said pre-computed
7 values to produce branch metrics.

1 16. The apparatus of claim 11, in which said branch metric processor comprises:
2 a symbol sequence generator for generating hypothetical symbol sequences;
3 means for combining the received signal samples with the channel tap
4 estimates and said estimate of impairment correlation properties to produce metric
5 multipliers $e(j,n)$ and for combining said channel tap estimates with one another and
6 said estimate of impairment correlation properties to produce metric multipliers $f(j,n)$
7 and $g(j,k,n)$; and for combining said metric multipliers with said hypothetical symbol
8 sequences to produce branch metrics.

- 1 17. The apparatus of claim 11, in which said branch metric processor comprises:
2 a symbol sequence generator for generating hypothetical symbol sequences;
3 means for combining said received signal samples with said channel tap
4 estimates and said estimate of impairment correlation properties to produce $Z(n)$
5 values and combining said channel tap estimates with one another and said estimate of
6 impairment correlation properties to produce $S(k,n)$ values and for combining said $Z(n)$
7 and $S(k,n)$ values with said hypothetical symbol sequences to produce branch metrics.
- 1 18. The apparatus of claim 11, in which said sequence estimation processor employs
2 the Viterbi algorithm.
- 1 19. A method for reducing the effects of signal fading, time dispersion, and interference
2 in a radio communications system, comprising the steps of:
3 (a) generating and transmitting a signal representing a transmitted symbol
4 sequence;
5 (b) receiving said signal on one antenna;
6 (c) processing said signal to produce received signal samples for said antenna
7 such that multiple signal samples per symbol period are produced;
8 (d) estimating channel taps for each of said antennas to produce channel tap
9 estimates;
10 (e) estimating impairment correlation properties to produce an estimate of
11 impairment correlation properties;
12 (f) forming branch metrics in a branch metric processor using said received
13 signal samples, said channel tap estimates, and said estimate of impairment correlation
14 properties; and
15 (g) employing said branch metrics in a sequence estimation algorithm to
16 estimate said transmitted symbol sequence.

1 20. A method according to claim 19, in which said forming step (f) comprises:
2 a) generating hypothetical symbol sequences;
3 b) combining the received signal samples with channel tap estimates and said
4 estimate of impairment correlation properties to produce metric multipliers $e(j,n)$;
5 c) combining said channel tap estimates with one another and said estimate of
6 impairment correlation properties to produce metric multipliers $f(j,n)$ and $g(j,k,n)$; and
7 d) combining said metric premultipliers with said hypothetical symbol sequences
8 to produce branch metrics.

1 21. A method according to claim 19, in which said forming step (f) comprises:
2 a) generating hypothetical symbol sequences;
3 b) combining the received signal samples with channel tap estimates and said
4 estimate of impairment correlation properties to produce metric multipliers $e(j,n)$;
5 c) combining said channel tap estimates with one another and said estimate of
6 impairment correlation properties to produce metric multipliers $g(j,k,n)$; and
7 d) combining said metric premultipliers with said hypothetical symbol sequences
8 to produce branch metrics.

1 22. A method according to claim 19, in which said forming step (f) comprises:
2 a) generating hypothetical symbol sequences;
3 b) combining said received signal samples with said channel tap estimates and
4 said estimate of impairment correlation properties to produce $Z(n)$ values;
5 (b) combining said channel tap estimates with one another and said estimate of
6 impairment correlation properties to produce $S(k,n)$ values; and
7 (c) combining said $Z(n)$ and $S(k,n)$ values with said hypothetical symbol
8 sequences to produce branch metrics.

1 23. An apparatus for reducing the effects of signal fading, time dispersion, and
2 interference in a radio communications system, comprising:
3 a digital transmitter for generating and transmitting a signal representing a
4 transmitted symbol sequence;
5 a receiver for receiving said signal on one antenna;
6 an analog to digital converter for converting said signal into received signal
7 samples for said antenna such that multiple signal samples per symbol are produced;
8 a channel tap estimator for estimating channel taps for each of said antennas to
9 produce channel tap estimates;
10 an impairment correlation estimator for estimating impairment correlation
11 properties to produce an estimate of impairment correlation properties;
12 a branch metric processor for forming branch metrics using said received signal
13 samples, said channel tap estimates, and said estimate of impairment correlation
14 properties; and
15 a sequence estimation processor employing said branch metrics to estimate
16 said transmitted symbol sequence.

1 24. The apparatus of claim 23, in which said branch metric processor comprises:
2 a symbol sequence generator for generating hypothetical symbol sequences;
3 means for combining the received signal samples with the channel tap
4 estimates and said estimate of impairment correlation properties to produce metric
5 multipliers $e(j,n)$ and for combining said channel tap estimates with one another and
6 said estimate of impairment correlation properties to produce metric multipliers $f(j,n)$
7 and $g(j,k,n)$; and for combining said metric multipliers with said hypothetical symbol
8 sequences to produce branch metrics.

- 1 25. The apparatus of claim 23, in which said branch metric processor comprises:
2 a symbol sequence generator for generating hypothetical symbol sequences;
3 means for combining said received signal samples with said channel tap
4 estimates and said estimate of impairment correlation properties to produce $Z(n)$
5 values and combining said channel tap estimates with one another and said estimate of
6 impairment correlation properties to produce $S(k,n)$ values and for combining said $Z(n)$
7 and $S(k,n)$ values with said hypothetical symbol sequences to produce branch metrics.




Figure 1




Figure 2




Figure 3




Figure 4

5/8




Figure 5

6/8




Figure 6




Figure 7

8/8




Figure 8

INTERNATIONAL SEARCH REPORT

National Application No

PCT/US 95/09484

A. CLASSIFICATION OF SUBJECT MATTER
 IPC 6 H04L25/03 H04B7/08

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 H04L H04B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US,A,5 319 677 (KIM YOUNGKY) 7 June 1994 see column 1, line 31 - line 46 see column 1, line 59 - column 2, line 15 see column 2, line 38 - column 3, line 34 see claims 1-5 ---	1,3-11, 13-25
A	PERSONAL COMMUNICATION - FREEDOM THROUGH WIRELESS TECHNOLOGY, SECAUCUS, NJ., MAY 18 - 20, 1993, no. CONF. 43, 18 May 1993 INSTITUTE OF ELECTRICAL AND ELECTRONICS ENGINEERS, pages 408-411, XP 000393208 KAZUHIRO OKANOUE ET AL 'NEW MLSE RECEIVER FREE FROM SAMPLE TIMING AND INPUT LEVEL CONTROLS' see page 410, left column, line 7 - right column, line 38 --- -/--	1,2,4-25

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- 'A' document defining the general state of the art which is not considered to be of particular relevance
- 'E' earlier document but published on or after the international filing date
- 'L' document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- 'O' document referring to an oral disclosure, use, exhibition or other means
- 'P' document published prior to the international filing date but later than the priority date claimed

'T' later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

'X' document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

'Y' document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

'&' document member of the same patent family

Date of the actual completion of the international search

16 November 1995

Date of mailing of the international search report

15.12.95

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
 NL - 2280 HV Rijswijk
 Tel. (+ 31-70) 340-2040, Tx. 31 651 epo nl.
 Fax (+ 31-70) 340-3016

Authorized officer

Canali, F

INTERNATIONAL SEARCH REPORT

national Application No

PCT/US 95/09484

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	<p>EP,A,0 425 458 (ERICSSON TELEFON AB L M) 2 May 1991.</p> <p>see column 1, line 4 - line 32 see column 2, line 1 - line 53 see column 3, line 49 - column 5, line 10 see column 7, line 36 - column 8, line 47 -----</p>	<p>1,2,4,6, 9,11-13, 18-25</p>

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 95/09484

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US-A-5319677	07-06-94	NONE	

EP-A-0425458	02-05-91	SE-B- 464902	24-06-91
		AT-T- 107102	15-06-94
		AU-B- 626471	30-07-92
		AU-B- 6549290	31-05-91
		DE-D- 69009674	14-07-94
		DE-T- 69009674	22-09-94
		ES-T- 2054326	01-08-94
		HK-A- 123194	18-11-94
		JP-T- 4502695	14-05-92
		SE-A- 8903526	25-04-91
		WO-A- 9107035	16-05-91
		US-A- 5164961	17-11-92
